

# SPECIFICATION SHEET



## DESCRIPTION 90 5025

- 13G HPPE cut resistant gloves, sandy nitrile double coating

## FEATURES AND BENEFITS

- Durable HPPE knitting with excellent cut resistance
- Anti-abrasion & anti-slip
- High performance cut resistant level secure against mechanical hazards
- Excellent grip in wet and oil environments



## APPLICATIONS

- Metal & Glass Handling
- Sharp small parts handling
- Automotive industry
- Wood working
- Sanitation&Recycling
- Transportation
- Warehousing
- Construction
- General maintenance



## CARE INSTRUCTIONS

- Machine wash in warm water with Detergent and Bleach. Rinse well and spin extract using high speed. Tumble dry on Low heat setting. Proper washing will inhibit odors caused by the growth of bacteria or mold.

## TECHNICAL DATA

Description	13G HPPE cut resistant gloves, sandy nitrile double coating
Materials	Liner: HPPE knit Coating: sandy nitrile dipping
Cuff Style	Elastic seamless knit
Color	Grey,Green,Blue...
Size	6/XS-12/XXXL
Length (cm)	22-28
Palm width (cm)	8.5-11.5
Packing	Printing logo, 12 pairs per bag,120 pairs per case

Tolerance: ±5mm

## STANDARDS

- CE CATEGORY: II Intermediary risk in accordance with:
- EN 420 / AS / NZS2161.2:2016 General Requirements
- EN 388 / AS / NZS2161.3:2016 Protection Against Mechanical Risks